

PRODUCT-DETAILS

# 168FLR1-B0240

## FUSED ELBOW HOUSING 8.3KV



### General Information

Extended Product Type	168FLR1-B0240
Product ID	7TAA124110R0026
EAN	0783786430970
Catalog Description	FUSED ELBOW HOUSING 8.3KV
Long Description	Molded Current Limiting Fuse Housing, Nominal Fuse Voltage Rating 8.3kV, Fuse Test Port - Two Capacitive Test Ports, Small Housing, Cable Insulation Diameter 0.635 inch - 0.905 inch / 16-23mm, Aluminum Conductor size 1/0 AWG Stranded/Compressed, 2/0 AWG Solid/Compact.

### Ordering

EAN	0783786430970
Customs Tariff Number	8535908020

### Dimensions

Product Net Weight	7.77 lb 3.524 kg
--------------------	---------------------

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Protect Light Duty Underground Distribution Systems
Brand / Label	Elastimold
Color	Black
Current Rating	200 A
Insulation Material	Yes, EPDM Rubber
Material	EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Loadbreak Fused Elbow Connector
Size	Length 16.87 inches from bottom to center of Bushing
Special Functions	Full-Range Current-Limiting Fusing with 50kA Interrupting Capability. Hotstick Operable 15kV Loadbreak Elbow Switching.
Standards	IEEE 386, ANSI C37.40, ANSI C37.41, ANSI C37.47
Temperature Range	-40 to +65 °C
UPC	783786430970
Voltage Rating	8.3 kV

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	168FLR1-B0240
Instructions and Manuals	168FLR1-B0240

## Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

