



YA25L2TC38, Compression Terminal, 1/0 AWG Cu, 2-Hole, 3/8" Stud, 1" Spacing, Standard Barrel

By Burndy
Catalog # YA25L2TC38

1/0 AWG, CU, 2 Hole, 3/8 Stud, 1 IN Spacing, Standard Barrel, Inspection Window



Features

- Barrel designed with internal chamfer at wire entry for smooth insertion of wire, preventing possible damage of the strands
- Standard barrel length is recommended for installations with limited space availability
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- 2-Hole design prevents rotation

Application

Wire Termination

Specifications

| | |
|------------------------------------|--------------|
| Buy American Compliant | No |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Industry Standard(s) | UL 486A-486B |
| Certification - ETL | No |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | Yes |
| UL Listed | Yes |

Conductor

| | |
|--|---------------|
| Conductor - Material | COPPER |
| Conductor - Copper Str Size | 1/0 AWG |
| Conductor - Copper Str Navy Size | 100 (61) Navy |
| Conductor - Copper Str Navy Size Range | 100 (61) Navy |
| Conductor Size | 1/0 AWG |
| Conductor - Copper Str Size Range | 1/0 AWG |
| Conductor Type | CODE |

Configuration

| | |
|--------------------------------------|---|
| Physical Attribute - Number of Holes | 2 |
|--------------------------------------|---|

Connector Type

STANDARD BARREL

Current

| | |
|-------------------|-------|
| Voltage - Maximum | 35000 |
| Voltage Rating | 35 kV |

Dimensions

| | |
|--|----------|
| Outside Diameter | 0.51 in |
| Dimension - Outside Diameter inch | 0.51 in |
| Dimension - L Length Overall mm | 79 mm |
| Dimension - Pad Width inch | 0.75 in |
| Dimension - Hole Size fraction | 3/8 |
| Dimension - Hole Size inch | 0.41 |
| Dimension - Hole Size mm | 10.4 mm |
| Bolt Size | 3/8 in |
| Dimension - Strip Length inch | 15/16 |
| Dimension - Stud Size fraction | 3/8 |
| Dimension - Stud Size inch | 3/8 |
| Dimension - B Length fraction | 7/8 in |
| Dimension - B Length inch | 0.88 in |
| Dimension - Z inch | 0.42 in |
| Physical Attribute - Tongue Angle | Straight |
| Dimension - Bolt Hole Size inch Length | 0.39 in |
| Dimension - Bolt Size fraction | 3/8 |
| Dimension - Bolt Size inch | 0.38 |
| Dimension - Length Overall inch | 3.10 in |
| Dimension - D inch | 1.83 in |
| Dimension - N inch | 0.41 in |

General

| | |
|----------------------------------|-----------------------------|
| Die Index | 12 |
| Trade Name | HYLUG™ |
| Sub Brand | HYLUG |
| Color Code | Pink |
| Physical Attribute - Tongue Type | Standard |
| Plated | Y |
| Feature - Barrel Type | Standard |
| Feature - Barrel Style | Chamfered;Skived |
| Type | Standard Barrel, Tin Plated |

| | |
|-------------------|----------------------|
| UPC 12 Digit | 781810503621 |
| UPC 14 Digit GTIN | 00781810503621 |
| Material | COPPER |
| Plating Type | Tin - Electro Plated |
| Finish Type | Tin-Plated |
| UPC | 781810503621 |

| | |
|-----------------------|----|
| Minimum Pack Quantity | 1 |
| Carton Quantity | 10 |

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)
[Installation Manual \[French, English\]](#)

Logistics



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-YA25L2TC38-SPEC-EN | REV 11/2025