

YSU4W8W, Heavy-Walled Aluminum Tube with Solid Barrier

By Burndy

Catalog # [YSU4W8W](#)



Heavy-walled AL tubing with solid barrier minimizes galvanic corrosion, Color Code:Blue (Side A), Brown (Color Code)

Features

- Heavy-walled aluminum tube with solid barrier minimizes galvanic corrosion of conductors
- Accommodates neutral strands of SE Service Entrance Conductors as well as others
- Installed with standard tooling, color-coded, and pre-filled with PENETROX Joint Compound and Stripsealed

Specifications

Standards - RoHS Compliance CM

Status

Certification - CSA Approved No

Conductor

Conductor - Copper Solid Size 4 AWG

A

Conductor - Copper Solid Size 8 AWG

B

Conductor - Copper Str Size A 5 AWG, 6 AWG

Conductor - Copper Str Size A 5 AWG-6 AWG

Range

Conductor - Copper Str Size B 10 AWG

Conductor - ACSR Str Size A 6 (6/1) Turkey AWG

Conductor - ACSR Str Size A 6 (6/1) Turkey AWG

Range

Conductor - AL Str Size A 5 AWG, 6 AWG

Conductor - AL Str Size A 5 AWG-6 AWG

Range

Conductor - AL Str Size B 10 AWG

Dimensions

Dimension - B Length inch 0.87 in

Dimension - Outside Diameter inch 0.65 in

Dimension - L Length Overall mm 51 mm

Dimension - Length Overall inch 2 in

General

Die Index

- 243
- BG or 5/8

Trade Name

LINKIT™

Plated

Y

Type

Service Entrance, Uninsulated, Center Stop

Prefilled Oxide Inhibitor

Y

UPC 12 Digit

781810142936

UPC 14 Digit GTIN

00781810142936

Material

Aluminum

Plating Type

Tin - Hot Dipped

UPC

781810142936

Color Code - Side A

Blue

Color Code - Side B

Brown

Logistics

Minimum Pack Quantity

100

Carton Quantity

200

Pallet Quantity

29600

Product Assets

[Catalog \[English\]](#)