

Representative Image

Catalog No. 262LR-C5240

Description: 25 LB ELB W/TP 1/0STRN .805-1.060

UPC No 75114192095

Home > Medium Voltage Utility Solutions > Elastimold > Electrical connector assembly

25kV 200 Amp, Loadbreak Elbow Connector with Test Point, .805 inch - 1.060 Inch Cable Insulation Diameter, 1/0 Stranded Wire Size, Bi-Metal Compression Lug.

Descriptors

Category	Electrical connector assembly
Special Features	28kV, 200 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Provision for hot stick operation. Provision for ground wire connection. Wide cable range with minimum number of sizes. Long bi-metal compression lug is standard. Non-corrosive capacitive test point.
Application	200 kV, 200 Amp

Specifications

Conductor Range	1/0 STR/COMPR AWG , 2/0 SOL/COMPT AWG
Material	Housing - EPDM Rubber
Color	Black
Voltage Rating	28 kV
Amperage Rating	200 A
Insulation	Yes, EPDM Rubber
Temperature Rating	-40 to +65 C
Environmental Conditions	All Weather Conditions

Classifications

Brand Name	ELASTIMOLD
Standard	ANSI/IEEE Standard 386

Dimensions

Size	9.03 inch (299.4 mm) X 8.20 inch (208.3 mm) not including probe, 2.86 inch (72.6 mm) Diameter

by ABB