GK6426, Cu Alloy Ground Clamp, 3 Cables to Rod or Pipe



By Burndy
Catalog # GK6426

3 Cables to Rod or Pipe, 4 AWG (ol. - 2/0 AWG Str., 3/8" Pipe, 5/8" - 3/4" Rod, 3/8" Stud

Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

Application

For Joining Three Equal Copper Cables To Rod Or Tube, Direct Burial In Earth Or Concrete

Specifications

Certification - ETL	No
Certification - UL Recognized	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - cULus	No
Certification - UL Listed Direct Burial	Yes
Industry Standard(s)	UL467
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor Size	#4 AWG Sol - 2/0 AWG Str
Conductor - Rod Size	• 5/8 in • 3/4 in

Dimensions

Package Height	0.000 in
Dimension - Height mm	71.4 mm
Dimension - Height inch	2.81 in
Package Weight	0.000 lb.
Dimension - Width mm	75 mm
Dimension - Width inch	2.94 in
Package Length	0.000 in
Package Width	0.000 in
Dimension - B Length inch	1.50 in
Bolt Size	3/8 in

Force Related

Installation Torque Recommended in-lb	240 LBS/in

General

Plated	No
Product Family	Grounding and Bonding Connectors>Copper Mechanical Grounding Connectors>Cable(s) to Ground Rod/Pipe/Tube (GAR/GD/GK)>Three Conductor (GK)
Sub Brand	MECHANICAL CONNECTOR
Product Type	Mechanical
UPC	781810233528
Type	Three Cables to Rod or Tube
Material Type - Screw	DURIUM™ Silicon Bronze
U Bolt Type	269
Material	Copper Alloy, Cast
Plating Type	Unplated
UPC 12 Digit	781810233528
UPC 14 Digit GTIN	00781810233528

Logistics

Pallet Quantity	1
Carton Quantity	12

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved