
BURNDY

KS25, Split Bolt Connector, Run/Tap: #4 AWG-1/0 AWG Str



By Burndy
Catalog # KS25

Copper Split Bolt, Cu: 4 AWG-1/0 AWG (Str) (Run & Tap)

Features

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

Application

For Direct Burial Applications In Earth Or Concrete, Copper

Specifications

Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	RUS
Certification - ETL	No
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - Copper Str Run Range	4 STR - 1/0 STR
Conductor - Copper Str Run	• 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0
Conductor - Copper Solid Run Range	4 AWG-1/0
Conductor - Copper Solid Run	2/0 AWG
Conductor - Copper Solid Tap Range	14 AWG-1/0
Conductor - Copper Solid Tap	2/0 AWG
Conductor - CopperWeld Solid Tap Range	2/0
Conductor - CopperWeld Solid Tap	2/0
Conductor - CopperWeld Solid Run Range	2/0
Conductor - CopperWeld Solid Run	2/0
Conductor - CopperWeld Str Tap Range	5 D AWG-2 A AWG
Conductor - CopperWeld Str Tap	• 5 D AWG • 5 P AWG • 4 A AWG • 4 D AWG • 4 N AWG • 4 P AWG • 3 A AWG • 3 J AWG • 3 K AWG • 3 N AWG • 3 P AWG • 2 A AWG
Conductor - CopperWeld Str Run Range	4 D AWG-2 A AWG
Conductor - CopperWeld Str Run	• 4 D AWG • 4 N AWG • 4 P AWG • 3 A AWG • 3 J AWG • 3 K AWG • 3 N AWG • 3 P AWG • 2 A AWG
Conductor Type	• CU C Solid-Run • CU C Str-Run • CU Weld C Solid-Run • CU Weld C Str-Run • CU C Str-Tap • CU Weld C Solid-Tap • CU Weld C Str-Tap • CU C Solid-Tap
Conductor - Copper Str Tap Range	4 STR - 1/0 STR
Conductor - Copper Str Tap	• 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0

Configuration

Connector Type	Split Bolt

Dimensions

Package Height	0.000 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	45 mm
Width	0.73 in
Dimension - Width fraction	73/100 in
Dimension - B Length fraction	83/100 in
Dimension - Width mm	19 mm
Dimension - Width inch	0.73 in
Dimension - B Length inch	.83 in
Dimension - Cross Flats inch	0.94 in
Dimension - Length Overall inch	1.77

Force Related

Installation Torque Recommended in-lb	385 in

General

Product Family	Power Connectors>Split Bolts>KS
Trade Name	SERVIT®
Plated	No
Sub Brand	SERVIT
Product Type	Mechanical
UPC	781810013106
Type	KS, Compact
Material	Copper
Plating Type	Unplated
UPC 12 Digit	781810013106
UPC 14 Digit GTIN	00781810013106

Logistics

Pallet Quantity	11600
Carton Quantity	50

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved