BURNDY

KS29

Por Burndy
No de catálogo KS29

Perno partido de cobre, Cu: 1 AWG (Str)-250 kcmil (Run & Tap)



Características

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

Aplicación

For Direct Burial Cables

Especificaciones

Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	• UL 486A • UL486B
Certification - ETL	No
Standards - Industry Standards Met	• UL 486A • UL486B
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	No

Relacionado con conductores

Conductor - Rebar Size	4
Conductor - Rebar Size Range	4
Conductor - Copper Str Run Range	1 STR - 250 KCMIL
Conductor - Copper Str Run	• 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil
Conductor - Copper Solid Run Range	1 AWG-250 kcmil
Conductor - Copper Solid Run	4/0 AWG
Conductor - Copper Solid Tap Range	8 AWG-250 kcmil
Conductor - Copper Solid Tap	4/0 AWG
Conductor - CopperWeld Solid Tap Range	4/0
Conductor - CopperWeld Solid Tap	4/0
Conductor - CopperWeld Solid Run Range	4/0
Conductor - CopperWeld Str Tap Range	7 #5
Conductor - CopperWeld Str Tap	7 #5
Conductor - CopperWeld Str Run Range	7 #5
Conductor - CopperWeld Str Run	7 #5
Conductor Type	• CU C Solid-Run • CU C Str-Run • CU Weld C Solid-Run • CU Weld C Str-Run • CU C Str-Tap • CU Weld C Solid-Tap • CU Weld C Str-Tap • CU C Solid-Tap
Conductor - Copper Str Tap Range	1 STR - 250 KCMIL
Conductor - Copper Str Tap	• 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil

Configuración

Connector Type	Split Bolt

Dimensiones

Package Height	0.000 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	53 mm
Width	1 in
Dimension - Width fraction	1-17/100 in
Dimension - Width mm	30 mm
Dimension - Width inch	1.17 in
Dimension - B Length inch	1.00 in
Dimension - Cross Flats inch	1.36 in
Dimension - Length Overall inch	2.25

Fuerza

Installation Torque Recommended	650 in in-lb

General

Trade Name	SERVIT®
Plated	N
Sub Brand	SERVIT
UPC	781810013809
Type	KS
Material	Copper
Plating Type	Unplated
UPC 12 Digit	781810013809
UPC 14 Digit GTIN	00781810013809

Logística

Pallet Quantity	4625
Carton Quantity	25

Documentación del producto

Catalog [English]

© 2026 Hubbell Incorporated. Todos los derechos reservados