Conector C-TAP de conexión a tierra por compresión YGHHC29C29



Por Burndy
No de catálogo YGHHC29C29

Conector a tierra de compresión, material: cobre, recorrido de rango: 3/0 Str-250 Kcmil, varilla de 1/2" o 5/8"; Grifo: 3/0 Str-250 Kcmil.

Características

- Double Figure C Connector, C-Shaped opening permits two continuous parallel cables into conductor groove
- Qualified to IEEE-837 2014
- Prefilled with PENETROX compound and strip sealed

Aplicación

For Direct Burial cables

Especificaciones

Standards - Industry Standards Met	• UL467 • IEEE 837 • IEEE 837 2014 Qualified • UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	Yes
Industry Standard(s)	• UL 467 • IEEE 837 • IEEE 837 2014 Qualified • UL 486A-486B
Certification - CSA Approved	[Delete]

Relacionado con conductores

Conductor - Rod Run Range	• 1/2" • 5/8"
Conductor - Copper Str Run Range	3/0 Stranded - 250 kcmil
Conductor - Copper Str Tap Range	3/0 Stranded - 250 kcmil

Configuración

Connector Type	Tap

Dimensiones

Package Height	0.000 in
Dimension - Height mm	0 mm
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in

General

Plated	No
Product Family	Grounding and Bonding Connectors>"Hyground" Compression Grounding Connectors>C-Taps
Trade Name	HYTAP™
Sub Brand	HYTAP
Die Index	997
Product Type	Compression
UPC	621945456242
Type	Taps
Material	Copper
UPC 12 Digit	621945456242
UPC 14 Digit GTIN	00621945456242

Logística

Pallet Quantity	3840
Carton Quantity	40

Documentación del producto

Catalog [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. Todos los derechos reservados