YS6C, Cu Compression Splice, Long Barrel, 6 AWG



By Burndy
Catalog # YS6C

6 AWG, CU, Long Barrel SPLICE

Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Certification - UL Recognized	No
Buy American Compliant	Yes
Certification - cULus	No
Buy America(n) Qualified	Buy American Act Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - Material	COPPER
Wire Size	#6 AWG
Conductor - Copper Str Size	6 AWG
Conductor Size	6 AWG
Conductor - Copper Solid Size	6 Sol.
Conductor Type	CODE
Conductor - Copper Str Size Range	6 AWG

Configuration

Connector Type	LONG BARREL

Current

Voltage Rating	35 kV
Voltage - Maximum	35000

Dimensions

Package Height	0.000 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	60 mm
Dimension - Strip Length inch	1-3/16
Dimension - B Length inch	1.09 in
Dimension - Length Overall inch	2.38 in

General

Product Family	COMPRESSION
Trade Name	HYLINK™
Die Index	7
Feature - Barrel Type	Long
Feature - Barrel Style	Chamfered
Plated	Yes
Color Code	Blue
Sub Brand	HYLINK
Product Type	Splice
UPC	781810507407
Type	YS, Long Barrel
Material	Copper
Plating Type	Tin
Finish Type	Tin-Plated
UPC 12 Digit	781810507407
UPC 14 Digit GTIN	00781810507407

Logistics

Minimum Pack Quantity	1
Carton Quantity	50

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved